

Communication Markets Division

# 3M™ No Polish LC/UPC Connector

## Singlemode and Multimode 250 μm/ 900 μm

3M™ No Polish LC Connector provides fast on-site termination of 250 μm and 900 μm terminations utilizing a one-piece, pre-assembled design.

The LC compatible connector consists of a factory-polished fiber/ferrule assembly and a mechanical splice that is terminated with a simple field tool. To maximize field installation yield, the splice in the connector can be opened and reused with a cap lifter, which is integrated with dust cap. The streamlined boot is attached to the connector body, minimizing the chance of losing it during the termination process. After the installation, the boot keeps the fiber from kinking, even during side pull.

On the 3M™ No Polish LC Connector Assembly Tool 8835-AT, the connector receptacle is hinged allowing for easy insertion and removal of the LC NPC connector.



3M™ No Polish LC/UPC Connector Family

The LC NPC Connector is tested for FTTP and Premises applications for indoor and outdoor locations and is RoHS compliant.\*

Features	Benefits
Field termination	Right cable length with virtually no cable slack to store
One-piece, pre-assembled design	No small, loose parts
Duplexing capability built into connector design	Separate duplex clip unnecessary
Factory-polished fiber stub	No on-site polish or adhesives required
900 μm buffer strain relief	Excellent pull out strength
Simple assembly tool	Fast and easy installation
Fiber holder for assembly	Aligns and guides fiber into connector with optimal insertion force





Close up of 3M™ No Polish LC Connector  
Assembly Tool 250/900 8835-AT

### 3M™ No Polish LC Connector Specifications


	Multimode 6830-50	Multimode 6830-50/LOMFF	Multimode 6830-62.5	Singlemode 8830
Insertion Loss (dB) typical	0.2	0.2	0.2	0.3
Reflectance (dB) typical at room temp	<-30	<-30	<-25	<-40
Reflectance (dB) over operating temperature range	<-30	<-30	<-25	<-35
Operating temperature range (°C)	-10°C to 60°C	-10°C to 60°C	-10°C to 60°C	-40°C to 75°C
Storage temperature (°C)	-40°C to 85°C	-40°C to 85°C	-40°C to 85°C	-40°C to 85°C
Connector identification				
Backbone	Black	Black	Black	Black
Housing	Black	Aqua	Beige	Blue
Boot	White	White	White	White
Field termination kit (no power needed)	8865-C	8865-C	8865-C	8865-C



The 3M™ No Polish Connector Kit with  
Cleaver 8865-C includes all tools necessary  
for termination



The 3M™ No Polish Connector Premium Kit  
with 3M Cleaver 8865-C/PR



3M™ Easy Cleaver is conveniently included  
in select packages of 3M™ No Polish LC  
Connectors

## Ordering Information - 3M™ No Polish Connectors

Product Number	Connector, Kit and Tool Descriptions	Packaging	3M ID
6830-50	No Polish LC Connector MM 50 µm 250/900 µm with tool (black trigger)	60/package	80-6113-2773-7
6830-50/LOMMF	No Polish LC Connector MM 50 µm LOMMF 250/900 µm with tool (aqua trigger)	60/package	80-6113-2774-5
6830-62.5	No Polish LC Connector MM 62.5 µm 250/900 µm with tool (beige trigger)	60/package	80-6113-2775-2
8830	No Polish LC Connector SM 250/900 µm with tool (blue trigger)	60/package	80-6113-2776-0
8835-AT	No Polish LC Connector Assembly Tool 250/900 µm	1/package	80-6113-2797-6
8865-C	No Polish Connector Preparation Kit with cleaver	1/package	80-6113-2379-3
8865	No Polish Connector Kit without cleaver	1/package	80-6113-23785
8865/PR	No Polish Premium Premium Kit without cleaver	1/package	80-6114-82961
8865-C/PR	No Polish Connector Premium Kit with cleaver	1/package	80-6113-8783-0

## Connectors with Easy Cleaver

8830/C	No Polish LC/UPC Connector SM with 3M™ Easy Cleaver	120/box	80-6114-9415-6
6830-50/C_60	No Polish LC Connector MM 50 µm with 3M Easy Cleaver	60/box	80-6114-9425-5
6830-50LOMMF/C_60	No Polish LC Connector MM 50 µm laser optimized with 3M Easy Cleaver	60/box	80-6114-9426-3
6830-62.5/C_60	No Polish LC Connector MM 62.5 µm with 3M Easy Cleaver	60/box	80-6114-9427-1

“RoHS 2011/65/EU” means that the product or part does not contain any of the substances in excess of the maximum concentration values (“MCVs”) in EU RoHS Directive 2011/65/EU. The MCVs are by weight in homogeneous materials. This information represents 3M’s knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.

3M is a trademark of 3M Company.

### Important Notice

All statements, technical information, and recommendations related to 3M’s products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M’s current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of 12 months from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M’s option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.



### Communication Markets Division

6801 River Place Blvd.  
Austin, TX 78726-9000 USA

Phone 1-800-426-8688  
Fax 1-800-626-0329  
Web 3M.com/Telecom

Please recycle. Printed in USA © 3M 2015.  
All rights reserved. 80-6114-9882-7