

Termination Box HTTP-Y24

General Information

Multipurpose fiber optic distribution-termination box HTTP-Y24 is designed to provide a flexible platform to address the multitude of applications that exist in residential and commercial FTTx installations. Can be deliver with pre-installed SC adapters. Easy to install and is capable of being mounted directly to standard electrical junction boxes or directly to wall. The box interior can be configured to address slack storage, splicing, cross connect or any combination. The Distribution box kit includes all the necessary accessories –parts for complete box installation.

Features

- Outdoor use
- Designed for Wall and Pole mount applications
- Available for SC or LC adapters (up to 24 Simplex SC or Duplex LC adaptors)
- Accepts loose tube, distribution cables
- Bend radius protection
- Rugged and durable construction for long term reliability (UV resistance)
- Resistance to vibration and shock
- Door with secure mechanism & Safety lock
- Can accommodate 1 x 8, 1 x 16 or 1 x 32 PLC Splitter
- Up to 24 drop cables
- Whole front operation
- Reusable
- Sheath retention & central strength member termination system included
- ROHS compliance



Specifications:

Model No.	Number of entry /exit ports	Spliced fiber storage capacity (single fusion)	PLC Splitter	Protection Class	Dimensions LxWxH(mm)
HTTP-Y24	3 ports: max diameter 14 mm 24 drop cable ports: diameter 3 mm	96 Splices (4x24 splices)	1x8; 1x16 1x32 Splitter	IP 65	306.7x245x81
Item Number	54212215				
Country of origin	China				